



# Taking Care of Your Tires.

www.premaproducts.com

Call Customer Service: 866-657-7362 (Toll Free)

## TPMS Service Kits & Replacement Stems Cross Reference 09/22/2022

PREMA USA Hamaton Product	Dill	31 Inc.	Alligator	Schrader	Torque Specifications
6-102	1070K	17-20107AK	591303	20004	Valve Core Torque: 3 - 5 inch lbs. - Nut Torque: 62 inch lbs. (7.0 Nm)
6-103	1080K	17-20028AK	591304	20003	Valve Core Torque: 3 - 5 inch lbs. - Nut Torque: 38 inch lbs. (4.25 Nm)
6-104	1060K	17-20096AK	591302	20002	Valve Core Torque: 3 - 5 inch lbs. - Nut Torque: 44 inch lbs. (5.0 Nm)
6-108	1050K	17-20201AK	591301	20030	Valve Core Torque: 3 - 5 inch lbs. - Nut Torque: 71 inch lbs. (8.0 Nm)
6-109	2000K	17-20206AK	591309	20021	Valve Core Torque: 3 - 5 inch lbs. - Nut Torque: 35 inch lbs. (4.0 Nm)
6-110	1090K	17-20211AK	591305	20023	Valve Core Torque: 3 - 5 inch lbs. - Nut Torque: 35.5 inch lbs. (4.0 Nm)
6-111	1100K	17-20216AK	591306	20032	Valve Core Torque: 3 - 5 inch lbs. - Nut Torque: 35 inch lbs. (4.0 Nm)
6-112	1130K	17-20005AK	591308	20005	Valve Core Torque: 3 - 5 inch lbs. - Nut Torque: 49 inch lbs. (5.5 Nm)
6-115	1030K	17-20202AK	591318	20017	Valve Core Torque: 3 - 5 inch lbs. - Nut Torque: 71 inch lbs. (8.0 Nm)
6-116T	1110K	17-20217AK	591307	20031	Valve Core Torque: 3 - 5 inch lbs. - Nut Torque: 35 inch lbs. (4.0 Nm)
6-117	1120K	17-20221AK	591314	20033	Valve Core Torque: 3 - 5 inch lbs. - Nut Torque: 44 inch lbs. (5.0 Nm)
6-120	2030K	17-20014AK	591312	20014	Valve Core Torque: 3 - 5 inch lbs. - Nut Torque: 58 inch lbs. (6.5 Nm)
6-121	1110K	17-20217AK	591307	20031	Valve Core Torque: 3 - 5 inch lbs. - Nut Torque: 35 inch lbs. (4.0 Nm)
6-122	2010K	17-20009AK	591310	20009	Valve Core Torque: 3 - 5 inch lbs. - Nut Torque: 44 inch lbs. (5.0 Nm)
6-123	1077K	N/A	N/A	20012	Valve Core Torque: 3 - 5 inch lbs. - Nut Torque: 53 Inch lbs. (6.0 Nm)
6-125	2020K	17-20015AK	591311	20015	Valve Core Torque: 3 - 5 inch lbs. - Nut Torque: 62 inch lbs. (7.0 Nm)
6-127	2040K	17-20204AK	591313	20019	Valve Core Torque: 3 - 5 inch lbs. - Nut Torque: 40 inch lbs. (4.5 Nm)
6-129	1031K	17-20207AK	591317	20017	Valve Core Torque: 8 Inch lbs. - Nut Torque: 71 inch lbs. (8.0 Nm)
6-134	2040K	17-20204AK	591313	20019	Valve Core Torque: 3 - 5 inch lbs. - Nut Torque: 35 inch lbs. (4.0 Nm)
6-136	2040K	17-20204AK	591313	20022	Valve Core Torque: 3 - 5 inch lbs. - Nut Torque: 35 inch lbs. (4.0 Nm)
6-137	1090K	17-20211AK	591305	20023	Valve Core Torque: 3 - 5 inch lbs. - Nut Torque: 62 inch lbs. (7.0 Nm)
6-138	7020K	17-20720AK	591315	N/A	Valve Core Torque: 3 - 5 inch lbs. - Nut Torque: 71 inch lbs. (8.0 Nm)
6-139	7000K	17-20700AK	591316	N/A	Valve Core Torque: 3 - 5 inch lbs. - Nut Torque: 71 inch lbs. (8.0 Nm)
6-201	N/A	N/A	N/A	N/A	Screw Torque: 8.85 inch lbs. - Nut Torque: 53 inch lbs. (6.0 Nm)
6-204	1097K	17-20035AK	590805	20035	Nut Torque: 35 inch lbs. (4.0 Nm)
6-206B	1040K	17-20203AK	591330	N/A	Nut Torque: 53 inch lbs. (6.0 Nm)
6-207	VS-950	17-20018	591320	20018	T-10 Screw Torque: 12.5 inch lbs. (1.4 Nm)
6-207-B	VS-20	17-20045	N/A	20046	T-10 Screw Torque: 12.5 inch lbs. (1.4 Nm)
6-208	VS-90	17-50397	N/A	20043	T-10 Screw Torque: 12.5 inch lbs. (1.4 Nm)
6-210	VS-20	17-20045	N/A	N/A	T-10 Screw Torque: 12.5 inch lbs. (1.4 Nm)
6-210H	VS-20	17-20046	N/A	20046	T-10 Screw Torque: 12.5 inch lbs. (1.4 Nm)
6-211	VS-65	17-50395	N/A	20635	T-10 Screw Torque: 12.5 inch lbs. (1.4 Nm)
6-215A	N/A	17-43016, 17-43046	N/A	N/A	T-10 Screw Torque: 12.5 inch lbs. (1.4 Nm)
6-218	1098K	17-20198AK	591322	N/A	Valve Core Torque: 3 - 5 inch lbs. - Nut Torque: 53 Inch lbs. (6.0 Nm)
6-220B	1092K	N/A	590337	20037	Screw Torque: 35.5 inch lbs. (4.0 Nm) - Nut Torque: 35.5 inch lbs. (4.0 Nm)
6-225	N/A	N/A	N/A	34000	Nut Torque: 53 inch lbs. (6.0 Nm) / T10 Scree Torque: 12.5 in-lbs. (1.4 Nm)
6-266	N/A	N/A	N/A	N/A	T10 Torque: Nut 35.5 in-lbs. - Screw 12.5 in-lbs.
6-266BK	N/A	N/A	N/A	N/A	T10 Torque: Nut 35.5 in-lbs. - Screw 12.5 in-lbs.
6-228T	9066K	17-20020AK	N/A	N/A	Nut Torque: 58 inch lbs. (6.5 Nm)
6-231C	VS-70	17-20725AK	591326	N/A	Nut Torque: 71 inch lbs. (8.0 Nm)
6-235	VS-40	N/A	N/A	20016	Nut Torque: 53.1 inch lbs (6.0 Nm)
6-236	VS-965	17-50391	591365	N/A	Nut Torque: 35.5 inch lbs. (4.0 Nm)
6-240	1096K	N/A	590801	N/A	Screw Torque: 35.5 inch lbs. (4.0 Nm) - Nut Torque: 35.5 inch lbs. (4.0 Nm)
6-270	VS-312	N/A	N/A	N/A	Torque: Nut 35.5 in-lbs. -T10 Screw Torque 12.5 in-lbs.
6-415/TPS-1-502C	VS-35	17-50396	N/A	N/A	Torque: Nut 35.5 in-lbs. -T10 Screw Torque 12.5 in-lbs.
6-437AL	VS-240 Alloy	N/A	N/A	N/A	Torque: Nut 35.5 in-lbs. -T10 Screw Torque 12.5 in-lbs.
6-439AL	VS-920	N/A	N/A	N/A	Torque: Nut 35.5 in-lbs. -T10 Screw Torque 12.5 in-lbs.
6-503	VS-30	17-20044	N/A	N/A	Torque - Clip Style
6-507	VS-15	N/A	N/A	N/A	T10 Screw Torque - 12.5 in-lbs
TPMS-416AL	VS-919	17-50392	N/A	N/A	Torque: Nut 35.5 in-lbs. -T10 Screw Torque 12.5 in-lbs.
TPS-412	N/A	17-50398	N/A	N/A	T10 Screw Torque - 12.5 in-lbs

### PREMA Service Kits/Stems: Alternative Parts

Primary Part	Alternate Part(s)	Primary Part	Alternate Part(s)
6-102	6-113, 6-118	6-146	6-144
6-110	6-137	6-206B	6-240
6-116T	6-121	6-207	6-207A, 6-213, 6-216
6-122	6-118	6-207-B	6-207, 6-210, 6-210H, 6-213
6-125	6-114, 6-127, 6-142T, 6-143T, 6-134, 6-136	6-210H	6-210
6-127	6-114, 6-125, 6-142T, 6-143T, 6-134, 6-136	6-220B	6-220, 6-221, 6-222B, 6-223B
6-139	6-139B	6-228T	6-228
		6-240	6-220B, 6-214, 6-242, 6-243